

## COOLING EQUIPMENT

### PNX-CPG-202-UC UPRIGHT GASTRONOM REFRIGERATOR - 2 FULL DOORS – COMPRESSOR UP



- Stainless steel exterior and interior body
- Cooling Temperature -2°C / +8°C
- High performance 43°C tropical conditions
- New Built-in touch digital controller for electronically temperature and defrost control.
- High performance Built-in LED light
- Hygienic ,specially pressed door Handel
- Wide internal volume
- Anti drop cable type heating resistant in the door frame
- Self closing doors at 90°
- “Ozone friendly” polyurethane insulation (60 mm thickness).
- Plastic coated adjustable interior shelves.
- Energy saving high insulated body with 40 kg/m<sup>3</sup> density.
- CFC free, R-290 A refrigerant gas.
- Ventilated, removable compressor.
- Gas condensation container.
- Fan cooling
- Unoxidized, antibacterial painted, evaporator with copper pipe and aluminum panel.
- Less cleaning demanding painted wire
- Condenser adapted to R-290 Gas
- Heat Insulated Tempered Glass in Glass Door Models
- Easy to clean Curved interior body,
- Stainless steel evaporator cover.
- New Solid Body

Interior Volume (lt):1600

#### Technical specifications

|                       |   |     |
|-----------------------|---|-----|
| Power                 | W | 280 |
| Electrical connection |   |     |
| 230 V – I + N + T     |   |     |

#### Dimension and Weight

|              |    |      |
|--------------|----|------|
| Length       | Mm | 700  |
| Depth        | Mm | 843  |
| Height       | Mm | 2080 |
| Net Weight   | Kg | 100  |
| Gross weight | Kg | 110  |

