

COOLING EQUIPMENT

PNX-CPP-202-UC-GD UPRIGHT PATISSERIE REFRIGERATOR - 2 FULL GLASS DOORS – COMPRESSOR UP



- Suitable for 40*60 Cm patisserie Trays
- Stainless steel exterior and interior body
- Cooling Temperature -2°C / +8°C
- High performance 43°C tropical conditions
- New Built-in touch digital controller for electronically temperature and defrost control.
- High performance Built-in LED light
- Hygienic ,specially pressed door Handel
- Wide internal volume –
Anti drop cable type heating resistant in the door frame
- Self closing doors at 90°
- “Ozone friendly” polyurethane insulation (60 mm thickness).
- Adjustable Patrisseri Tray Guides
- Energy saving high insulated body with 40 kg/m³ density.
- CFC free, R-290 A refrigerant gas. -
Ventilated, removable compressor.
- Gas condensation container.
- Fan cooling
- Unoxidized, antibacterial painted, evaporator with copper pipe and aluminum panel.
- Less cleaning demanding painted wire
Condenser adapted to R-290 Gas
- Heat Insulated Tempered Glass in Glass Door Models
- Easy to clean Curved interior body,
- Stainless steel evaporator cover.
- New Solid Body

Interior Volume (lt):1600

Technical specifications

Power	W	400
Electrical connection		
230 V – I + N + T		



Dimension and Weight

Length	Mm	1600
Depth	Mm	843
Height	Mm	2080
Net Weight	Kg	266
Gross weight	Kg	276