

COOLING EQUIPMENT

PNX-CPP-202-UC UPRIGHT PATISSERIE REFRIGERATOR - 2 FULL DOORS – COMPRESSOR UP



<ul style="list-style-type: none"> - Suitable for 40 x60 Cm patisserie Trays - Stainless steel exterior and interior body - Cooling Temperature -2°C / +8°C - High performance 43°C tropical conditions - New Built-in touch digital controller for electronically temperature and defrost control. - High performance Built-in LED light - Hygenic ,specially pressed door Handel - Wide internal volume - Anti drop cable type heating resistant in the door frame - Self closing doors at 90° - "Ozone friendly" polyurethane insulation (60 mm thickness). - Adjustable Patrisseri Tray Guides 	<ul style="list-style-type: none"> - Energy saving high insulated body with 40 kg/m³ density. - CFC free, R-290 A refrigerant gas. - Ventilated, removable compressor. - Gas condensation container. - Fan cooling - Unoxidized, antibacterial painted, evaporator with copper pipe and aluminum panel. - Less cleaning demanding painted wire Condenser adapted to R-290 Gas - Heat Insulated Tempered Glass in Glass Door Models - Easy to clean Curved interior body, - Stainless steel evaporator cover. - New Solid Body
--	--

Interior Volume (lt):1600

Technical specifications

Power W 400
Electrical connection 230 V – I + N + T



Dimension and Weight

Length	Mm	1600
Depth	Mm	843
Height	Mm	2080
Net Weight	Kg	250
Gross weight	Kg	260